


**Datasheet**
**AXIOM5151**
**OCXO with Ultra-Low PHASE NOISE Floor of -180 dBc/Hz**

 Rev. 3  
 Date: 2014-05-08

**FEATURES**

- Connectorized Package, size 51 x 51 x 19 mm.
- Ultra-Low Phase Noise up to -180 dBc/Hz
- Sine wave Output level
- Standard frequencies : 100.000 / 120.000 MHz

51 x 51 x 19 mm. max.



Parameter	min.	typ.	max.	Unit	Condition
Frequency range	80		125	MHz	
Standard frequencies	100.000 / 120.000			MHz	
Frequency stability					
Initial tolerance @ 25°C			± 300	ppb	@V <sub>C</sub> = 5.0 V
vs. operating temperature range			± 200	ppb	steady state (Note 2)
vs. supply voltage variation (pushing)		± 20		ppb	V <sub>S</sub> ± 5%
Long term (aging) per day			± 2	ppb	after 30 days operation
long term (aging) 1 <sup>st</sup> year			± 200	ppb	after 30 days operation
Frequency adjustment range					
Electronic Frequency Control (EFC)	± 1	± 2		ppm	
EFC voltage V <sub>C</sub>	0	5.0	10.0	V	
EFC slope (Δf / ΔV <sub>C</sub> )	positive				
EFC input impedance	100			kΩ	
RF output					
Signal waveform	Sine wave				R <sub>L</sub> = 50 Ω
Output level	+ 14	+ 16		dBm	@V <sub>C</sub> = 5.0 V
Harmonics			-40	dBc	
Spurious			-110	dBc	
Phase noise	See table 1				
Noise floor			-180	dBc/Hz	@ ≥ 100 kHz
Warm-up time @ 25°C			5	min	Δf <sub>final</sub> /f <sub>0</sub> < ±0.2 ppm
G-Sensitivity			1.0	ppb/g	per axis
Supply voltage V <sub>S</sub>	11.4	12	12.6	V	Note 3
Current consumption (steady state)			275	mA	@ +25°C
Current consumption (warm-up)			475	mA	
Operating temperature range	-10		+60	°C	Note 2
Weight			85	g	
Packing	Palette				
Enclosure (see drawing) (LxWxH)	51x51x19 max.			mm	See drawing

**Notes:**

1. Terminology and test conditions are according to IEC standard IEC60679-1 and MIL-PRF-55310, unless otherwise stated
2. Other stability and temperature range on request
3. Other supply voltage on request

**Absolute Maximum Ratings:**

Parameter	min.	max.	Unit	Condition
Supply Voltage V <sub>S</sub>	- 0.5	V <sub>S</sub> + 10%	V	V <sub>S</sub> to GND
Control Voltage V <sub>C</sub>	- 0.5	15	V	V <sub>C</sub> to GND
Storage Temperature	-55	+125	°C	

Datasheet

**AXIOM5151**

**OCXO with Ultra-Low PHASE NOISE Floor of -180 dBc/Hz**

**Phase Noise - Option 1:**

Offset	100 MHz					120 MHz					Unit
	A	B	C	D	E	A	B	C	D	E	
10 Hz	-90	-95	-97	-100	-105	-85	-90	-95	-97	-100	dBc/Hz
100 Hz	-125	-130	-132	-135	-137	-118	-122	-125	-127	-130	dBc/Hz
1 kHz	-155	-158	-160	-162	-164	-148	-150	-153	-155	-157	dBc/Hz
10 kHz	-175	-176	-176	-176	-178	-160	-165	-168	-171	-175	dBc/Hz
≥100 kHz	-180	-180	-180	-180	-180	-180	-180	-180	-180	-180	dBc/Hz

**Table 1**

**Ordering Code:**

Model (Specification)	Option 1 (Phase Noise)	Revision	Frequency [MHz]
AXIOM5151	Table 1	Rev.3	100.000

**Example: AXIOM5151-C\_Rev.3 - 100.000MHz**

**Environmental conditions:**

Test	IEC 60068 Part ...	IEC 60679-1 clause ...	MIL-STD-202G Method	MIL-STD-810F Method	MIL-PRF-55310D Clause	Test conditions (IEC)
Sealing tests (if applicable)	2-17	5.6.2	112E		3.6.1.2	Gross leak: Test Qc, Fine leak: Test Qk
Solderability	2-20	5.6.3	208H		3.6.52	Test Ta Method 1
Resistance to soldering heat	2-58		210F		3.6.48	Test Td <sub>1</sub> Method 2 Test Td <sub>2</sub> Method 2
Shock*	2-27	5.6.8	213B	516.4	3.6.40	Test Ea, 3 x per axes 100g, 11 ms half-sine pulse
Vibration, sinusoidal*	2-6	5.6.7.1	201A 204D	516.4-4	3.6.38.1 3.6.38.2	Test Fc, 30 min per axes, 10 Hz - 55 Hz 0,75mm; 55 Hz - 2 kHz, 10g
Vibration, random*	2-64	5.6.7.3	214A	514.5	3.6.38.3 3.6.38.4	Test Fdb
Endurance tests - ageing - extended aging		5.7.1 5.7.2	108A		4.8.35	30 days @ 85°C, OCXO @25°C 1000h, 2000h, 8000h @85°C

**Handling and Testing:**


Parameter	Procedure		Condition
Electrostatic discharge (ESD)			
THD devices	IEC60749-26	HBM	2000V
SMD devices	IEC607749-27	MM	200V
Washable	Yes		
RoHS-Compliant	Yes		

Datasheet

AXIOM5151

OCXO with Ultra-Low PHASE NOISE Floor of -180 dBc/Hz

Enclosure drawing :



Pin connections:

Pin #	Symbol	Function
1	V <sub>s</sub>	Supply Voltage
2	N.C.	No Connection
3	GND	Ground
4	V <sub>c</sub>	Control Voltage (EFC)
SMA	RF OUT	RF Output

Rev. 3 date 2014-05-08